



Doc. Nr. TDS_4-400







Version: 2024_01

1K PLASTIC PRIMER 4-400

Eurolux 1K Plastic Primer 4-400 is a one component adhesion Primer for almost all plastics used in automotive industry. An excellent adhesion primer for plastic bumpers, spoilers, car parts and other plastic objects or surfaces such as ABS, PA, EP-laminate, PC, PBT, POM, PPO, PP/EPDM, PUR, PVC. Fast drying. Overpaintable with Eurolux 1K and 2K Lacquers and Primers.

Colour: Transparant.

Only for professional use.

	Mixing ratio (by volume)	-		
	Sprayviscosity, DIN 4, at 20°C	12 s		
	Application method	1,2 – 1,3 mm 1,6 – 2,0 bar		
	Number of spraycoats	1 ; Film thickness 3 – 5 µm		
	Flash off at 20°C	-		
	Drying time at 20°C:	Recoatable 10 min.		
	Theoretical coverage	8 - 10 m ² /l		
	Storage	Keep away from sources of ignition. Store separately from flammable substances. Keep container tightly closed in a dry, cool and well ventilated place. Storage temperature above 3°C.		
	Shelf-life	3 years		

The in this leaflet supplied details and advises are based on our experiences and best knowledge. The user will be deemed to have satisfied himself independently of the suitability of the product for his own particular purpose. Guarantees cannot be claimed from this leaflet.